

Product	Type
LUBRISTAY™ 9750	Metal Processing Oil Soluble Extreme Pressure and Lubricity Additive

Application

Lubristay 9750 is an oil soluble, potassium triborate extreme pressure and anti-wear additive for industrial oils, greases and gear lubricants. It can be used alone or in combinations with other anti-wear and extreme pressure additives.

Lubristay 9750 will not stain yellow metals and is thermally stable.

Typical Properties (Not Specifications)

Test	Typical
Appearance	Amber brown viscous liquid
Specific Gravity @25°C	1.12
Boron Content, wt. %	7
Viscosity @ 25° C, cPs	450

Applications

Lube and gear oils, greases, metalworking lubricants, industrial oils

Storage and Handling

Recommended Maximum Long Term Storage Temperature*	Must be ambient. 1 year shelf life. Avoid freezing. Mix prior to use
Flash Point	>150° C

Lockhart Chemical Company

4102 James P Cole Boulevard Flint, MI 48505

Phone: 1-810-789-8330 Fax:1-810-789-3266

www.lockhartchem.com

email: customerservice@lockhartchem.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given